



ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



AQUA-ELITE

PREMIUM WATER BASED PENETRATING SEALER

Aqua-elite delivers premium protection against staining. Aqua-elite can be used for pre-sealing prior to grouting and can be used all year round especially in the cooler months due to its water-base technology.

*ALWAYS TEST FIRST

5 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.




APPLICATION



Apply 2 – 3 coats of AQUA-ELITE with a Lambswool Applicator or Viton Sprayer.



COVERAGE



Approx. 10m² per litre per coat

Environex International Pty Ltd

PO Box 1298 Wangara WA 6065, 19 Motivation Dr, Wangara WA 6065

T +61 8 9302 4000 **ABN** 37 159 887 117 **W** www.environex.net.au





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators

PREMIUM BLUESTONE SEALER

Specially Formulated Penetrating Sealer for Bluestone

PREMIUM BLUESTONE SEALER is a natural penetrating sealer for Bluestone and other masonry.

*ALWAYS TEST FIRST

5 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.




APPLICATION



Apply 2-3 thin coats using an Environex Lambswool Applicator or Environex Viton Seal sprayer.



COVERAGE



Approx. 10m² per litre per coat

Environex International Pty Ltd

PO Box 1298 Wangara WA 6065, 19 Motivation Dr, Wangara WA 6065
T +61 8 9302 4000 **ABN** 37 159 887 117 **W** www.environex.net.au





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



CLEARSEAL

Permanent Water Barrier & Grout Pre-Seal

CLEARSEAL is an easy to use, single coat water-based sealer, designed to repel water on most masonry surfaces. It will assist in the prevention of moss & mold build-up and is an excellent pre-seal or pre-grout treatment for very porous surfaces such as Sandstone and Terracotta.

*ALWAYS TEST FIRST

5 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.



APPLICATION



Apply ONLY 1 coat of CLEARSEAL to masonry or pavers to block water. A second coat or pooling may cause whitening.



COVERAGE



Approx. 10m² per litre per coat





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



ENDURE

Wet Look Sealer For Stone & Masonry Surfaces

ENDURE is a unique blend of premium acrylic resins formulated especially for application to most coarse stone, masonry and concrete surface, giving a wet look and protection against staining from most common spills.

*ALWAYS TEST FIRST

5 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.




APPLICATION



Apply 2-3 thin coats using an Environex Lambswool Applicator. Applying a thick coat may make the surface slippery.



COVERAGE



Approx. 10m² per litre per coat





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



BEFORE

AFTER

GRAFFITI SHIELD F ANTI - GRAFFITI PROTECTION

GRAFFITI SHIELD F acts against the penetration of moisture and airborne pollutants into masonry and concrete surfaces.

*ALWAYS TEST FIRST

6 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.




TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.




APPLICATION



Two coats should be applied 24 hours apart. GRAFFITI SHIELD F can be applied by brush, roller or airless spray.



COVERAGE



Approx. 6 - 8 m² per litre per coat. For non-absorbent surfaces, the spread rate can be as high as 12 sq meters.



DRYING & CURING TIME



Full stain resistance develops after 48 hours.





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



HI-LITE

Highlights the Natural Characteristics of the Stone

HI-LITE is a premium semi-penetrating sealer that enhances stone color without making surfaces too slippery. Ideal for internal, external use on honed natural stone and polished block walls.

*ALWAYS TEST FIRST

6 EASY STEPS




SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.




APPLICATION



Apply 2-3 thin coats using an Environex Lambswool Applicator OR Viton sprayer.



COVERAGE



Approx. 10m² per litre per coat



DRYING & CURING TIME



Allow 8 hours after final coat before walking or using the surface.





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



SYNERGY

CSIRO TESTED Consolidator/Penetrating Sealer

SYNERGY is a high-performance consolidator and penetrating sealer for superior stain and salt protection, ideal for pool areas and all surface types. To reduce salt damage, install a 40mm overflow pipe 150mm below pool coping to prevent frequent submersion.

*ALWAYS TEST FIRST

6 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.




SURFACE PREP



Ensure surface is clean and dry.



APPLICATION



Apply a minimum of 2 coats. Note 3 - 5 coats may be required in salt-exposed environments. Use a lambswool applicator or an Environex Viton sprayer for best results.



COVERAGE



Approx. 10m² per litre per coat



DRYING & CURING TIME



Full stain resistance develops after 24 hours (suitable for foot traffic after 2 hours), with complete curing and consolidation achieved after 7 days.





ENVIRONEX INTERNATIONAL



The Next Generation in Specialty Formulators



TUSCAN TSL

Premium Natural Look Penetrating Sealer

TUSCAN TSL is a low-VOC, eco-friendly penetrating sealer that protects against stains. Suitable for all areas, indoor and outdoor.

*ALWAYS TEST FIRST

6 EASY STEPS



SAFETY



Wear PPE safety glasses, mask, gloves, and boots. Protect clothing.



TEMPERATURE



Do not seal below 10°C or above 30°C.



SURFACE PREP



Ensure surface is clean and dry.




APPLICATION



Apply 2 – 3 coats of TUSCAN TSL with a Lambswool Applicator or Viton Sprayer.



COVERAGE



Approx. 10m² per litre per coat



DRYING & CURING TIME



Full stain resistance develops after 24 hours (suitable for foot traffic after 2 hours).

Environex International Pty Ltd

PO Box 1298 Wangara WA 6065, 19 Motivation Dr, Wangara WA 6065
T +61 8 9302 4000 **ABN** 37 159 887 117 **W** www.environex.net.au

